

3U CPCle Dual Gigabit Ethernet

Product #OSS-CPCle-ETH-3U



Specifications

Form factor	• IEEE 1386 single wide CMC)
Ethernet controller	• One or two Intel 82546EB (2 or 4 ports) • IEEE 802.3 and IEEE 802.3u (Ethernet and Fast Ethernet) • IEEE 802.3ab (Gigabit Ethernet) • IEEE 802.1q (VLAN insertion & removal)
Power requirements	• > 7.5W
Environmental operating	• Temperature: -5 to 60°C (23 to 140°F) • Humidity: 5 to 90% non-condensing
Environmental Storage	• Temperature: -40 to 70°C (-40 to 158°F) • Humidity: 0 to 95% non-condensing
Pending certifications	• FCC Part 15 Subpart B • UL1950, Listed Accessory • CS003 • CS03
Drivers	• Linux • Windows

Description


3U CompactPCI Express dual Gigabit Ethernet controller board with PCI Express x4 interface on rear connector and two RJ-45 connectors on front panel.

Product Features

- Two or four auto-negotiating 10/100/1000 Ethernet ports
- Single or dual Intel 82546 MAC/PHYs on single PMC slot
- 33/66 MHz and 32/64-bit PCI 2.2 bus interface
- Link and activity LEDs
- Drivers for Linux and Windows

Ordering Information

Product #OSS-CPCle-ETH-3U
 sales@onestopsystems.com
 Call Toll Free! 1-877-438-2724



www.onestopsystems.com

Phone 877-438-2724 • Fax 760-466-1678 • sales@onestopsystems.com