



## CompactPCI Express x4 HIB

Product #OSS-CPCle-3U-HIB2-x4



### Specifications


<b>Form Factor</b>	• 3U or 6U
<b>Front Panel Connectors</b>	• One PCIe x4 cable connector
<b>Front Panel Indicators</b>	• Power On / Cable Present LEDs
<b>Front Panel EMI Connector Shield</b>	• Molex 74540-0100
<b>Dimension (H x L)</b>	2.7" H x 3.4" L (68 x 86mm)
<b>Power Consumption</b>	• 3.75W typical, 3.3@1.3A
<b>Environmental Operating</b>	<ul style="list-style-type: none"> <li>• Temperature: 0° to 50°C (32° to 122°F)</li> <li>• Humidity: 10 to 90% non-condensing</li> <li>• Shock: 30g acceleration peak (11ms pulse)</li> <li>• Vibration: 5-17 Hz 0.5" double amplitude displacement; 7-2000Hz, 1.5g acceleration, no cable connected</li> </ul>
<b>Redriver</b>	• Pericom PI2EQX4402D
<b>Power Supply</b>	<ul style="list-style-type: none"> <li>• 12V±5%</li> <li>• 5Vaux</li> </ul>
<b>Agency Compliance</b>	<ul style="list-style-type: none"> <li>• UL60950, FCC Class B, CE safety and emissions</li> <li>• Designed to meet, but not tested</li> </ul>

### Product Features

- PCI Express x4 cable connector on face plate
- Power on/cable present LEDs
- No Software Drivers Required
- PICMG EXP.0 system slot compliant
- x4 PCI Express PCI-SIG compliant cable uplink
- 10 Gbps cable bandwidth
- 3U or 6U form factor

### Ordering Information

CompactPCI Express x4 HIB  
 Product #OSS-CPCle-HIB2-x4  
 sales@onestopsystems.com  
 Call Toll Free! 1-877-438-2724



[www.onestopsystems.com](http://www.onestopsystems.com)

Phone 877-438-2724 • Fax 760-466-1678 • sales@onestopsystems.com