



## Rackmount

Product #OSS-PCI-2U-ENCL-XXXX-300



### Specifications

<b>Mounting</b>	• 19in. rack mount (482.6mm)
<b>Dimensions</b>	• (W x H x D): 17in. x 3.48in. x 23in. (432 x 88.4 x 612mm)
<b>Front Panel</b>	• Indicators: Power on LED (Green) • Hard drive activity LED (Yellow)
<b>Front Panel Controls/ Connections</b>	• Power on/off switch • System reset switch
<b>Drive Capacity</b>	• Two 5.25-inch front-accessible drive mounts • Six 3.5-inch front-accessible drive mounts
<b>Cooling Fans</b>	• Two 50.6CFM fans
<b>Air Filter</b>	• One 30 ppi (pores per inch) air filter, open cell, polyfoam, UL 900 rating
<b>Construction</b>	• Clear zinc plated (20 and 18 gauge) cold rolled steel
<b>Color</b>	Black front, medium texture paint
<b>Weight</b>	37pounds (16.7kg)
<b>Power Supply Specifications</b>	• 320 watt output • ATX form factor • Ball bearing fan UL, CSA and TUV approved • Outputs: 5V @ 32A, 3.3V @ 20A, +12V @ 11A, -12V @ 1A, -5V @ 1A • Total Max 5V & 3.3V: 160W
<b>Operating Environment</b>	• Temperature Range: 0 ° to 50 °C (32 ° to 122 °F) • Relative Humidity: 10 to 90% non-condensing • Shock: 30g acceleration peak (11ms pulse) • Vibration: 5-17 Hz 0.5" double amplitude displacement; 7-2000Hz, 1.5g acceleration

### Description

2U enclosure with 5-slot PCI backplane, 300W PS, drives not included.

### Features

- 2U high x 17 inches wide x 23 inches deep
- 300 watt ATX power supply
- 5-slot passive backplane, (2) PICMG, (4) PCI
- (2) 5.25 inch drive bays, up to (6) 3.5 inch drive bays
- (2) card cage fans
- Front-to-rear air flow
- Optional rack slides



[www.onestopsystems.com](http://www.onestopsystems.com)

Phone 877-438-2724 • Fax 760-466-1678 • [sales@onestopsystems.com](mailto:sales@onestopsystems.com)