



Rackmount

Product # OSS-PCI-4U-ENCL-XXXX-700



Specifications


Backplane	PICMG 1.3 SHB Express compliant with one ELB and 19 PCI Express x4 (x8 connectors)
Mounting	• 19in (482.6mm)
Dimensions (W x H x D)	• 17 x 5.25 x 23in
Front Panel Indicators	• Power on LED (Green) • Hard drive activity LED (Yellow)
Front Panel Controls/ Connections	• Power on/off switch • System reset switch
Drive Capacity	• Three 5.25-inch front-accessible drive mounts
Cooling Fans	• Five 50.6CFM fans
Air Filter	• One 30 ppi (pores per inch) air filter, open cell, polyfoam, UL 900 rating
Construction	• Clear zinc plated (20 and 18 gauge) cold rolled steel
Paint	• Black front, medium texture paint or to customer's specification
Weight	• 65 pounds (16.7kg)
Power Supply Specifications	• 350 watt output • 100/240 VAC 50/60HZ • Auto sensing • UL, CSA and TUV approved • Outputs: 5V @ 32A, 3.3V @ 20A, +12V @ 11A, -12V @ 1A, -5V @ 1A • Total Max 5V & 3.3V: 160W

Description

4U high pasive backplane-based enclosure with dual 350 watt power supplies, and your choice of passive backplane.

Features

- Dual redundant 350 watt power supplies
- Up to four 5-1/4 inch drive bays and up to six 3-1/2
- Superior cooling with five fans and removeable air filters
- Supports up to 19-slot PICMG-compatible passive backplanes
- XXXX- in part number indicates backplane selected



www.onestopsystems.com

Phone 877-438-2724 • Fax 760-466-1678 • sales@onestopsystems.com