



ONE STOP  
SYSTEMS

# PCIe Cable

With crossover cabling, the connectors on either end of the PCIe x4 cable are identical. Each connector is equipped with a retractor allowing the connector to be locked into place. OSS-PCIe-CBL-x4

- PCIe x4 cable
- Available in 1m, 2m, 3m, 5m and 7m lengths

- PCI-SIG PCI Express Cable Specification Compliant
- Includes x4 PCIe lanes and side-band signals for:
  - Power-on
  - Reset
  - SM Bus (clock/data)
  - 100MHz Reference clock
  - Board Present
  - Wake

- Positive latching mechanism per the PCI-SIG specification
- Supports 10 Gbps full-duplex transfer rates



## TECHNICAL SPECIFICATIONS

### PCIe Cable

Cable Length	1m, 2m, 3m, 5m, 7m
Circuits (Loaded)	38
Gender	Male-Male
Lock to Mating Part	Yes
Material - Metal	Zinc Alloy
Packaging Type	Bag
Pitch - Mating Interface	0.80mm (.031")
Single Ended	No
Waterproof / Dustproof	Yes
Wire Insulation Diameter	N/A
Wire Size AWG	28
Wire/Cable Type	Round
<b>Electrical</b>	
Current - Maximum per Contact	1A
Shielded	Yes
Voltage - Maximum	30V DC



www.onestopsystems.com