

# CUBE

The CUBE desktop enclosure supports one double-wide or two single wide full-height I/O card(s) up to 13.25" long and includes a PCIe cable adapter and cable or Thunderbolt cable and 180-watt power supply.

PN: OSS-PCIe-ENCL-EXP-CUBE

## Features

- Increases system's functionality
- Supports one double-wide or two single-wide full-height PCIe cards up to 13.25" long
- Ample cooling and power
- Easy installation
- Connects via PCIe or Thunderbolt
- No additional drivers required (other than those required for the add-in card)



## Specifications

Enclosure	9.7"H x 3.35"W x 14.4" D Front Panel LED Weight: 3.5 lbs.
Slots	One PCIe x16 or Two PCIe x8 Gen3
Power Supply	180W power supply (external)
Connectivity	Thunderbolt, PCIe x1, x4, x8, x16, or Gen3 x16 and 1M PCIe cable or .5M Thunderbolt cable
Cooling	One low CFM fan
Operating Environment	0-50°C 10-90% relative humidity 0-10,000 feet above sea level
Storing Environment	-40 to 85°C 5-96% relative humidity 0-50,000 feet above sea level
Agency Compliance	UL, FCC Class A Canada ICES-003 Canada NMB-003 CE

# CUBE2

The CUBE2 desktop enclosure supports up to five single-wide or two double-wide and one single-wide full-height I/O cards up to 13.25" long and includes a PCIe cable adapter, Express Card, or Thunderbolt cable and a 550-watt power supply.

PN: OSS-PCIe-ENCL-EXP-CUBE2-5

## Features

- Increases system's functionality
- Supports up to five single-wide or two double-wide full-height PCIe cards up to 13.25" long
- Ample cooling and power
- Easy installation
- Connects via PCIe or Thunderbolt
- No additional drivers required (other than those required for the add-in card)



## Specifications

Enclosure	9.7"H x 6.25"W x 14.4" D Front Panel power on LED Weight: 11 lbs
Slots	Five PCIe x4 Gen2
Power Supply	550W power supply (internal)
Connectivity	Express Card x1 or x4, PCIe x1, x4, x8, x16 or Gen3 x16 and a 1M PCIe cable, or .5M Thunderbolt cable
Cooling	One low CFM fan
Operating Environment	0-50°C 10-90% relative humidity 0-10,000 feet above sea level
Storing Environment	-40 to 85°C 5-96% relative humidity 0-50,000 feet above sea level
Agency Compliance	UL, FCC Class A Canada ICES-003 Canada NMB-003 CE

# CUBE3

The CUBE3 desktop enclosure supports up to eight single-wide or four double-wide full-height I/O cards up to 13.25" long and includes a PCIe cable adapter and cable or Thunderbolt cable and two 550-watt power supplies.

PN: OSS-PCIe-ENCL-EXP-CUBE3-8

## Features

- Increases system's functionality
- Supports up to eight single-wide or four double-wide full-height PCIe cards up to 13.25" long
- Ample cooling and power
- Easy installation
- Connects via PCIe or Thunderbolt
- No additional drivers required (other than those required for the add-in card)



## Specifications

Enclosure	9.7"H x 9.21"W x 14.4" D Front Panel LED Weight: 12.5 lbs
Slots	Eight PCIe x4 Gen3 OR Eight PCIe x8 Gen3
Power Supply	Dual 550W power supplies (internal)
Connectivity	Express Card x1 or x4, PCIe x1, x4, x8, x16 or Gen3 x16 and a 1M PCIe cable, or .5M Thunderbolt cable
Cooling	Two high CFM fans
Operating Environment	0-50°C 10-90% relative humidity 0-10,000 feet above sea level
Storing Environment	-40 to 85°C 5-96% relative humidity 0-50,000 feet above sea level
Agency Compliance	UL, FCC Class A Canada ICES-003 Canada NMB-003 CE