

PCIe x4 Cable

With crossover cabling, the connectors on either end of the PCIe x4 cable are identical. Each connector is equipped with a retractor allowing the connector to be locked into place.

PN: OSS-PCIe-CBL-x4

Features

- PCIe x4 cable
- Available in 1m, 2m, 3m, 5m and 7m lengths
- PCI-SIG PCI Express Cable Specification Compliant
- Includes x4 PCIe lanes and side-band signals for:
 - Power-on
 - Reset
 - SM Bus (clock/data)
 - 100MHz Reference clock
 - Board Present
 - Wake
- Positive latching mechanism per the PCI-SIG specification
- Supports 10 Gbps full-duplex transfer rates



Specifications

| | |
|---|--------------------|
| Cable Length: | 1m, 2m, 3m, 5m, 7m |
| Circuits (Loaded): | 38 |
| Gender: | Male-Male |
| Lock to Mating Part: | Yes |
| Material-Metal: | Zinc Alloy |
| Packaging Type: | Bag |
| Pitch-Mating Interface: | 0.80mm (.031") |
| Single Ended: | No |
| Waterproof/Dustproof: | Yes |
| Wire Insulation Diameter: | N/A |
| Wire Size AWG: | 28 |
| Wire/Cable Type: | Round |
| Electrical Current – Maximum per Contact: | 1A |
| Shielded: | Yes |
| Voltage- Maximum: | 30V DC |