



1U Compute Accelerator with NVIDIA Tesla GPUs

The CA2000 Compute Accelerator with one or two NVIDIA® Tesla® GPU accelerators is employed in a variety of HPC applications including oil and gas exploration and financial services. Completely integrated with the GPUs most suited for a specific application, it's easy installation and tested reliability makes it superior to alternative products. The CA2000 occupies only 1U of rack space and connects to the host server through the latest technology PCIe x16 Gen3 connection.

PN: OSS-PCIe3-1UX



Features

- 1U High
- One Rear Panel PCIe x16 Gen3 Interface
- Remote System Monitoring Capability; monitor fans, temperature and voltages
- 1620-watt Power Supply
- Superior Cooling with Eight 30 CFM Fans
- Choice of 1 or 2 NVIDIA Tesla GPUs

Specifications

Enclosure	
Dimensions	1.75"H x 17"W x 22.25" D Front Panel LED One Rear panel PCIe x16 interface
Capacity	Up to two NVIDIA Tesla GPUs
Power Supply	1620W power supply (internal)
Expansion	PCIe x16 1-meter cable PCIe x16 Gen3 cable adapter
Cooling	Eight 30 CFM fans (removable)
Operating Environment	0-35°C 10-90% relative humidity 0-10,000 feet above sea level
Storing Environment	-40 to 85°C 5-96% relative humidity 0-50,000 feet above sea level
Agency Compliance	Pending: FCC Class A CE RoHS

	Tesla M40	Tesla M60	Tesla P100	Tesla V100
Peak Double Precision Performance	.2 TeraFLOPS	3.8 TeraFLOPS	4.7 TeraFLOPS	7.8 TeraFLOPS
Peak Single Precision Performance	7 TeraFLOPS	7.4 TeraFLOPS	9.3 TeraFLOPS	15.7 TeraFLOPS
Number of GPUs	1 Maxwell GM200	2 Maxwell GM204s	1 Pascal GP100	1 Volta GV100
Number of CUDA Cores	3072	4096	3584	5120
Memory Capacity and Bandwidth	24GB GDDR5 at 288GB/s	16GB GDDR5 at 320GB/s	16GB CoWoS HBM2 at 720GB/s or 12GB CoWoS HBM2 at 540GB/s	16GB HBM2 at 900GB/s
Power Consumption	250 W	300 W	300 W	250 W